



# GLIDDEN TRADE ANTI-SLIP FLOOR PAINT

## G306

### PRODUCT INFORMATION

<b>Typical Use</b>	<p>Glidden Trade Anti-Slip Floor Paint is a professional quality, ready-mixed anti-slip floor coating that provides a consistent textured finish. Suitable for interior and exterior use on concrete, wood and metal surfaces.</p> <p>Particularly suited for access ramps, staircases, walkways, etc.</p> <p>Before preparing any surface for painting, read the Health Safety &amp; Environmental information on page 2 about old lead-based paints.</p>
<b>Codes according to the List of Wastes Regulations</b>	<p>Product as supplied: Assigned as hazardous waste code 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
<b>Pack Size</b>	5 litre only.
<b>Colour Range</b>	Grey, Red, Green, Yellow and Black.
<b>Film Properties</b>	<p><b>Chemical Resistance:</b> Resistant to mild chemical fume attack but where there is likely to be spillage of solvents, chemicals, cutting oils, dairy products, foodstuffs, etc. specialist coatings are likely to be required.</p> <p><b>Heat Resistance:</b> Generally resistant to heat up to 90°C.</p> <p><b>Water Resistance:</b> Resistant to repeated and regular washing with water and detergents but not suitable for use on floors that are likely to be continuously wet.</p>
<b>Composition (nominal)</b>	<p><b>Pigment:</b> Lightfast Non Lead Pigments.</p> <p><b>Binder:</b> Alkyd.</p> <p><b>Solvent:</b> White Spirit.</p>
<b>Volume Solids</b>	59% (nominal).
<b>Thinning</b>	New or bare porous surfaces should be sealed with a thinned coat of conventional smooth finish Glidden Trade Floor Paint, that has been thinned with up to 1 part white spirit to 10 parts of paint. <b>DO NOT THIN</b> Glidden Trade Anti-Slip Floor Paint.
<b>Application Method</b>	Brush or roller. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.
<b>Film Thickness</b>	<p><i>Film thickness will be dependent on the coverage achieved.</i></p> <p><b>Wet:</b> 125 microns.</p> <p><b>Dry:</b> 74 microns.</p>
<b>Drying Times</b>	<p><i>Single coat at standard thickness:</i></p> <p><b>Touch Dry:</b> 1 hour.</p> <p><b>Recoat:</b> 6 hrs. For light traffic use after 24 hrs. For moderate use after 48 hrs. Drying times will be extended at low temperatures. Full hardness is not reached for 7 days. Try to avoid excessive wear and tear during this period.</p>
<b>Practical Coverage</b>	On smooth surfaces of average porosity a litre of paint is sufficient to apply one coat to an

# GLIDDEN TRADE ANTI-SLIP FLOOR PAINT

# G306

area of up to 8m<sup>2</sup>.

## Cleaning Up

After use, remove as much paint as possible from brushes before cleaning with white spirit. Do not use or store in extremes of temperature.

## SURFACE PREPARATION

Surfaces must be clean, dry (less than 5.5 on Protimeter screed scale) and free from all defective or poorly adhering material. New or bare porous surfaces should be sealed (see thinning above). **DO NOT THIN** Glidden Trade Anti-Slip Floor Paint.

**Note:** Do not use in areas of heavy industrial use, aggressive environments, car showrooms or garage floors that are in prolonged contact with wet vehicle tyres or on power float/case hardened concrete or where silicate hardeners have been used, Terrazzo and Granolithic or substrates that have not fully dried out or do not incorporate an effective damp-proof membrane. This material is intended for light industrial/domestic situations. Some concrete floors may take up to 12 months to dry in depth. Do not use in areas of constant high humidity such as shower rooms and swimming pools etc.

## SYSTEM INFORMATION

**Stir thoroughly before use.**

The normal recommendation is to apply 2 coats of Glidden Trade Anti-Slip Floor Paint.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

### SOLVENT-BASED PAINT

**Flammable.**

**Repeated exposure may cause skin dryness or cracking.**

Contains: cobalt carboxylate, ethyl methyl ketoxime. May produce an allergic reaction.

Keep away from sources of ignition - no smoking.

Contains white spirit. Use only in well ventilated areas. Ensure maximum ventilation during application and drying.

When applying by brush or roller to large interior surface areas or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Before use refer to the safety data sheet.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

EU limit value for this product (cat. A/i): 600 g/l (2007)/500g/l (2010).

This product contains max.450g/l VOC.

See [www.glidden.co.uk](http://www.glidden.co.uk)

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, Glidden Oval and the ICI Roundel are trademarks of AkzoNobel.

© AkzoNobel 2010 (08112010 SDSG306IT)

